

## IPS Repeater

Art. no.:  
22002709



- No Ethernet required
- Relay data to receivers

### IPS Repeater

Normal IPS Receivers are connected to the server via Ethernet which is the most convenient solution. But sometimes installing a new cable is not an option due to cable lengths, walls, or simply costs. For those cases, we build the IPS Repeater.

This device can receive signals from our IPS Beacons like the normal receiver but instead of sending this data via Ethernet, it sends out the data wirelessly to another (standard) receiver. You only need 24V at the location of the repeater.



## IPS Repeater

Art. no.:  
22002709



## Technical Specification

Operating Principle	Wireless Indoor Positioning Repeater
Operating Frequency	2.45 GHz ISM band
Antenna Connector	Proprietary 2.4 GHz Link
Operating Voltage	24V DC
Temperature Range	-20Â°C to +75Â°C
Ingress Protection	IP42

## About Metratec

Metratec develops, produces and sells Radio electronics for the areas of "Identification", "Localization", and "Communication" and thus serves a variety of markets with standard products as well special solutions. Customers include OEM customers, system integrators and research facilities worldwide.

Metratec GmbH  
Niels-Bohr-Str. 5  
39106 Magdeburg, Germany  
T: +49 (0)391 251906-00  
Mail: [sales@metratec.com](mailto:sales@metratec.com)  
[www.metratec.com](http://www.metratec.com)

US Office  
Metratec USA  
6 Liberty Square #2073  
02109 Boston, MA, United States  
T: +1 (857) 799-3795  
Mail: [us@metratec.com](mailto:us@metratec.com)

